


Nättaggregat AGG 24V 15A 1U



Nättaggregat AGG 24V 15A 1U är ett rackmonterat nättaggregat som kan användas fristående eller tillsammans med Redundancy Panel 1U.

ANVÄNDNINGSSOMRÅDE

För att strömförsörja passersystem, låssystem och brandlarm och andra anläggningar som drivs med 24V DC.

Technical data

Recommended environment and the product's enclosure:	
Recommended environment:	Environment Class 1, Inhouse, 20% ~ 90% relative humidity
Ambient temperature:	+5 °C - 40 °C (For optimal battery life +15 °C - +25 °C)
Protection Class:	IP20
Recommended mounting:	Rack (angles included)
Dimension (HxWxD):	44x438x132mm (1U)
Net Weight:	2,3kg
The color of the enclosure:	Black
Built in fan for cooling:	Yes
Electrical information:	
Input voltage:	110V-264VAC/47-63Hz
Output voltage:	24VDC
Max Current:	15A
Rated power:	360W
Ripple at normal operation:	150mVp-p
Efficiency:	87%
Heat generation at 50% / 80% of rated power:	31W / 49W
Input Current:	1,8A
Number of fused outputs:	1pcs
Type of fuse output:	1xD20A
Protection against:	Overload, Overvoltage, Overtemperature & Short circuit
Alarm functions (1 output):	Power failure & load fuse failure
Alarm through:	Alternating relay
Article information:	
Article name:	Power supply 24V 15A 1U
Article number:	1U01D10024P1501
E-number:	5213517
The product meets:	EMC Directive 2014/30EU, Low Voltage directive: 2014/35/EU CE directive according to 765/2008, Emission: EN61000-6-2:2001, EN55022:1998-A1:2000, A2:2003 Class B, EN61000-3-2:2001. Immunity: EN61000-6-2:2005, EN61000-4-2, -3, 4, -5, -6, -11.
Warranty period / Rules for warranty:	2 years
Designed and produced by:	Milleteknik AB
Country of origin:	Sweden