



The MCT62E is an access terminal dedicated to RACS 5 access control and building automation system. Terminal enables identification of users by means of EM 125 kHz card. It can be installed in outdoor locations without any additional protection measures. The MCT62E is aligned with RADIUS series product line.

Features:

- power supply 11-15 VDC
- average current consumption 50 mA
- access terminal for RACS 5
- EM 125 kHz reader
- reading distance up to 8 cm (for ISO size cards)
- three LEDs
- buzzer
- RS485
- outdoor environment
- IP65
- RADIUS product line design
- tamper
- environmental conditions of operation:
 - temperature from -25°C to +60°C
 - humidity from 10% to 95%
- dimensions: 100.0 x 40.0 x 25.0 mm (height x width x thickness)
- weight: ≈100.0 g
- CE mark

Order guide	
<i>Item</i>	<i>Description</i>
MCT62E	EM 125 kHz access terminal

Legal Notice

This document is not intended to be a technical specification of the product and has informative character only. The Manufactures of product reserves right to change its characteristic without notice. The product features listed in this document refer to the entire series and depends on particular product version, configuration and additional equipment.

RevA © 2017 ROGER sp. z o.o. sp. k. All rights reserved.

This document is a subject to the Terms of Use in their current version published at the www.roger.pl