radius



PRT64EM-VP

Each PRT64EM-VP series reader can be used as an universal identification point connected to the access controller or configured for autonomous work, as a simple access controller for a single door. In the first case, the reader's functionality is limited only to reading an identifier (card/PIN) and sending data to an external controller, which takes further action. In case of work in a standalone mode, PRT64EM-VP terminals can independently supervise a single door using data entered in the process of their configuration.



Features:


- EM 125 kHz cards
- Programmable data output format
- Formats: Wiegand 26-66bit, Magstripe (Clock and data), RS232, RACS (Roger) and others
- Various ways of PIN and keypad codes transmission
- LED and Buzzer controlled through separate inputs
- Outdoor installation
- Can be used for Q5 card programming (required licensed version of RARC program)
- Programmed manually or from PC
- Free managing software (RARC)
- May operate as an offline standalone access controller

- 120 indexed users
- Authentication: Card and/or PIN
- Event log for 3000 transactions
- Built-in programmable 1.5A/30V relay output
- Two NO/NC inputs
- Two transistor outputs
- Operation with XM-2 I/O extension module
- Possible connection of the external PRT series reader (two way door control)
- Tamper
- CE mark

PRT64EM-VP views and installation diagram







Available versions and symbols	
Symbol	Description
PRT64EM-VP	Metal case and keypad, silver-metallic

Technical Specification	
Parameter	Value
Supply voltage	10-15 VDC
Current consumption (average)	85mA
Anti-sabotage protection (Tamper)	NC contact, 50mA/24V, IP67
Reading distance	Up to 8 cm
Environmental class	Class IV, outdoor-general, temperature: -25°C- +60°C, relative humidity: 10 to 95% (non condensing)
Dimensions H x W x D	115 X 80 X 35 mm
Weight	≈470g
Approvals	CE

ROGER sp.j Gościszewo 59 82-400 Sztum Poland **T.** +48 55 272 0132

F. +48 55 272 0133

E. roger@roger.pl

I. www.roger.pl

