



## AN-868-2PIN External antenna

The AN-868 external antennas are designed **to extend the communication range of wireless devices of the Jablotron security system using a frequency of 868 MHz.**

○ [Declaration of conformity - AN-868-2PIN \(PDF 315.87 kB\)](#)

### Description

The special design of the PIFA type provides the antenna with not only very good transmitting properties on different bases, but also tamper detection in the case of interruption or short-circuiting of the power supply (this functionality must be supported by the connected device). The antenna is suitable for both indoor and outdoor environments.

The AN-868-2PIN version is connected using a 2-pin connector that is used in devices of older systems and the present components of the JABLOTRON 100+ system.

### Compatible products

JABLOTRON 100+:

- JA-151A
- JA-151N
- JA-150IR
- JA-151IR
- JA-157P
- JA-158P
- JA-159P
- AC-116

JA-80 Oasis:

- UC-82
- JA-80Z
- JA-82R
- AC-8014
- AC-8007
- GD-04R

### Technical specifications

**Communication band**

868 MHz

**Antenna gain**

max. 3 dBi

<b>Impedance</b>	50 Ω
<b>Connection cable length</b>	1.9 m
<b>Dimensions (H x W x D)</b>	130 x 50 x 30 mm
<b>When a JABLOTRON alarm system is used:</b>	
<b>Classification</b>	security grade 2/Invironmental class IV Note: valid only for AN-868 in combination with device, which detect a sabotage of external antennae.
<b>- according to</b>	EN 50131-1, EN 50131-5-3
<b>- operational temperature range</b>	-20 °C až +60 °C
<b>- maximal operational humidity</b>	90% RH, non condensing