

## SPECIAL SOLUTIONS



Provision-ISR's special series aid the security professional facing the most unusual requests. The series includes discrete, c-mount, fisheye, Wireless, and PIR cameras, wireless adaptors, horn speakers, and a temperature testing unit.



# DB-320WIPN

## IR / WHITE LED DOORBELL CAMERA

Ideal for door-side installations, this 2MP doorbell camera with built-in white and IR LEDs, microphone, and speaker is a perfect solution for any residential home or office. DB-320WIPN also has a doorbell button that immediately opens a line of communication with the CAM2 app. When in use, you get a high-quality color image at any given time, and when combined with a face recognition NVR, you increase security by knowing who is at your door.



### MAIN FEATURES

- 2MP
- 1920 x 1080 Resolution
- 3D-DNR
- Face detection
- Built-in Microphone + Speaker
- white Light LED

### ANALYTICS

- Face detection



## SPECIFICATIONS

Video	Image Sensor	1/2.8" CMOS
	Effective Pixels	1920 x 1080 (16:9)
	Electronic Shutter	1/2s ~ 1/100000s
	Frame Rate	1-25/30FPS
	Day & Night	ICR
	Min. Illumination	0 lux (white LED on)
Audio	Audio compression	G.711A/G.711U
	Communication	2-way Audio
Image Enhancement	Image Settings	AWB, AGC Adjustable, Exposure Mode (Auto) Sharpness, Saturation, Brightness & Contrast Adjustable
	Image Enhancement	Digital WDR, BLC, HLC, ROI
	Noise Reduction	3D-DNR
	Image Orientation	N/A
	Privacy Zone	Yes
	Motion Detection	Yes
Compression	Video Compression	H.265 / H.264 / MJPEG (Substream only)
	Resolution	2MP (1920x1080) / D1 (704x576) / CIF (352x288)
	Multi-Stream	Master Stream: 2MP (1920x1080) / 1MP (1280x720) (1~30fps) Substream: 720P/D1/CIF (1~30fps)
	Bit rate	64Kbps ~ 8Mbps@H.265 / 64Kbps ~ 8Mbps@H.264
	Encode Mode	VBR/CBR
	Image Quality	Five levels under VBR; Free adjustment under CBR
	Analytics	Face Detection

## SPECIFICATIONS

Network	Remote Monitoring	IE Browsing, Ossia VMS Software, Provision Cam2 Mobile App
	User Access	Supports simultaneous monitoring of up to 3 users with multi-stream real-time transmission
	Network Protocol	IPv4, IPv6, TCP, UDP, DHCP, NTP, DDNS, 802.1X, RTSP, UPnP, Email, FTP, HTTPS
	ONVIF	Yes
	Ethernet	100Mbps
	PoE	Yes
Housing	Bracket	No
	Dimensions	150mm×50mm×29.8mm
	Weight(gross)	~145g
	Network	RJ45 (+PoE), WIFI(2.4G)
	Power	DC wiring
	Analog Video Output	No
	Audio Connectivity	Built-in Microphone + Speaker
	SD Card	Event/Schedule based Main/Substream recording (Up to 256GB)
	Hard Reset Button	Yes
	Dorbell Button	Yes
	Alarm	1 Alarm in
	Exit Button	Yes
	Door Unlock	1 NO 1 NC
	3rd Party unlock	1 Alarm in
	Wiegand	Yes (1 input + 1 output)
	Power Supply	DC12V/~500mA / PoE/~5.4W
	Work Enviroment	-20°C~50°C, 10%~90% Humidity
Junction Box	N/A	

## DIMENSIONS

