

DEC-0104(1U)

1 HDMI INPUT / 4 HDMI OUTPUT 144CH STANDALONE/OSSIA CMS DECODER

The ideal solution for control rooms. Provision-ISR DEC-0104(1U) decoder makes the difference when it comes to durability. The decoder can display up to 144 channels on 4 separate screens, taking the most resource-demanding task from the client – to itself. By doing so, the client is left free to deal with the CCTV unexpected tasks such as handling events, playback, alarms, etc... Each of the 144 windows is dynamic: the user can choose if to use it as a live window, playback window, or an alarm pop-up window!



MAIN FEATURES



https://provision-isr.com



SPECIFICATIONS

| WORK MODES | | |
|--------------------|---|--|
| Standalone | In Standalone mode, the user can add IP cameras to the decoder and set the decoding task | |
| Ossia VMS Platform | In Ossia VMS Platform mode, the decoder will be added to the Ossia VMS platform. All devices and task assignment are done via the Ossia VMS clients | |
| INTERFACE | | |
| Display Output | 2 x HDMI (4K/1080P/1280x1024), 2 x HDMI (1080P/1280x1024) 4 x VGA (1080P/1280x1024) 4 x CVBS (Analog) | |
| Display Input | 1 x HDMI (Up to 1080P) | |
| Audio Output | 4 x RCA | |
| Audio compression | 1 x Audio input1, 1 x Audio output (3.5mm audio interface, level: 2.0Vp-p, 1KΩ) | |
| LAN | 2 x 1Gbps (Load Balancing and Hot Standby) | |
| USB | 1 x USB3.0 + 1 x USB2.0 | |
| Alarms | 8 x Input + 8 x Output | |
| Serial Ports | 1 x RS-485, 1 x RS-232 | |
| PERFORMANCE | | |

| PERFORMANCE | |
|--|---|
| Decoding Resolution | 8MP / 5MP / 4MP / 4MP / 2MP / 1MP / WD1 / D1 / CIF |
| Video Decoding Format | H.265 / H.264 |
| Audio Decoding Format | G.711A / G.711U |
| Decoding Capability (Total Viewed Channels) | 4Ch - Up to 8MP 5-16Ch - Up to 4MP17-64Ch - D1>64ch - CIF |
| FPS | 1~50FPS (PAL), 1-60FPS(NTSC) |
| USB | 1 x USB3.0 + 1 x USB2.0 |
| Local Decoding Capability | 144ch |

| GENERAL | |
|-----------------------|----------------------------|
| Installation | Standard 19" Rack Mount |
| Power | 12VDC / 2A |
| Operation Temperature | Working: -20°C ~ 50°C |
| Protection Rate | None (Indoor Installation) |

DEC-0104(1U)



| Dimensions | 380*268*45mm |
|------------|--------------|
| Net Weight | ~2Kg |